



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Itaru Fukushima
Satoshi Yamanushi
Yuuki Horigome
Takehiko Saito

Title : Printer

Serial No. : 09/964,503

Filed : September 28, 2001

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231

VERIFICATION OF TRANSLATION

Sir :

I, Masao Watanabe, residing at 39-1 Kamiimasuwa, Shirane-cho, Nakakoma-gun, Yamanashi-ken 400-0211 Japan, declare that I am fluent in Japanese and English, and that herewith submitted English translation of Japanese specification is an accurate literal translation.



Date November 14, 2001

09964503-12231

TITLE OF THE INVENTION

PRINTER

BACKGROUND OF THE INVENTION

1. Field of the Invention:

[0001] The present invention relates to a printer for printing images and the like on recording media such as photosensitive recording sheets, particularly to a printer for printing on a plurality of recording media effectively and continuously.

2. Description of the Prior Art:

[0002] Prior printers make exposure on a photosensitive recording sheet before pressing it to develop, thereby forming an image on a surface of the photosensitive recording sheet. As an example, Japanese Patent Application Publication 2000-147678(A) discloses a recording apparatus as printer that: a photosensitive recording sheet called the Cycolor media is used that is formed of lamination of microcapsules filled with either one of coloring materials of cyan, magenta, and yellow each; the photosensitive recording sheet has a light of desired wavelength irradiated to a surface thereof to expose a color image; in other words, the surface is made to react to a light of specific wavelength to cure a sensitive material filled in the microcapsule together with the coloring material; the curing makes coloring reaction of the coloring material inactive; after that, a high pressure is applied to the active microcapsule without reacting to the light of specific wavelength to destroy for development (coloring), thereby forming the color image.

[0003] The prior printer mentioned above has an advantage that a running cost for printing can be kept low as consumable materials such as toner and ink or ink ribbon are not needed except for the above-mentioned Cycolor media only for forming, or printing, the color image. However, it has a problem pointed out that it takes a long time to print on a single photosensitive recording sheet (Cycolor media) as the pressing and developing processes have to be made after some stabilization time called

the dark time required after the exposing process.

[0004] To shorten the processing time, the above-mentioned prior printer is modified to make the sheet feeding and exposing processes in such a parallel way that a plurality of retaining tables for holding the photosensitive recording sheet is formed of a polyhedron, the retaining tables form a cyclic arrangement having a feedable first position for feeding the recording sheet, a second position for exposing the image to the fed recording sheet, and a dischargeable third position. The way can shorten the process time for the plurality of photosensitive recording sheet while allowing for the dark time.

[0005] However, even the above-described prior art has problems still that the apparatus is made large as wide space is needed in the apparatus for containing the plurality of retaining tables formed of polyhedron, and also an additional driving arrangement for operating the cyclic arrangement is needed, and further a complicated control system is needed for the cyclic operation of the plurality of retaining table. As a result, it would be involved in high apparatus manufacturing cost, or cost increase.

[0006] With respect to shortening a continuous process time for a plurality of media, various prior arts have been disclosed and put to practical use in a variety of fields and apparatuses. As an example, Japanese Patent Application Publication Hei 5-97305(A) discloses a technique being capable of making a processing speed higher, or shorten a processing time, by using a sheet inversing unit having a switchback path that controls a feed timing for the sheets fed successively, thereby allowing overlapping feed of the successive sheets on the switchback path.

OBJECT OF THE INVENTION

[0007] An object of the present invention is to provide a printer for printing a plurality of recording media successively that no large-scale arrangements are provided for printing processes to meet a required printing accuracy and to shorten a processing time.

[0008] Another object of the present invention is to provide a printer of low

price by way of suppressing apparatus manufacturing costs with use of simple feed driving arrangements and controls.

[0009] Still another object of the present invention is to provide a printer that no large-scale arrangements are provided for printing processes to meet a required printing accuracy and to shorten a processing time.

SUMMARY OF THE INVENTION

[0010] Briefly the foregoing objects are accomplished in accordance with aspects of the present invention by a printer, comprising in combination for forming an image on a surface of a recording media: preprocessing means for preprocessing the surface of the recording media to form an image on the surface of the recording media; post-processing means for post-processing the surface of the recording media preprocessed by the preprocessing means to form the image on the surface of the recording media; a recording media feed path formed between the preprocessing means and the post-processing means; first feed means arranged on an upstream side of the recording media feed path; and, second feed means arranged on a downstream side of the recording media feed path; wherein the first feed means and the second feed means are made different in driving control from each other. Driving supply to the second feed means may be run while driving supply to the first feed means is stopped, thereby feeding the preceding recording media to the post-processing means.

[0011] The printer further comprises in combination: a switchback section for substantially extending the recording media feed path wherein the second feed means is provided in the switchback section. The switchback section has a switchback path installed therein vertically and the second feed means is arranged on the switchback path and has a switchback driving arrangement for independently driving the second feed means.

[0012] A switching gate is provided between the first feed means and the second feed means on the recording means feed path for switching a feed direction for the recording media, the switching gate being movable between

a first position for guiding the recording media fed by the second feed means to the post-processing means and a second position for opening the upstream side and the downstream side on the recording media feed path for allowing the recording media to be transferred from the first feed means to the second feeding means. The second feed means may comprise a reversible feed roller and the switching gate may be positioned at the first position in synchronous with either of normal or reverse rotation of the feed roller.

[0013] The preprocessing means may have an exposing section for making exposure on the recording media and the post-processing means may have a developing section for making development by pressing the recording media having the exposure made thereon by the exposing section. It is preferable that the developing section has a pressure roller for pressing the recording media at a specific pressure and for feeding the recording media and a feed speed of the recording media fed by the pressure roller is slower than a feed speed of the recording media fed by the first and second feed means.

[0014] The printer further comprises in combination: a cutting section for cutting edges of the recording media developed by the developing section and third feed means for feeding to the cutting section the recording media developed by the developing section. It is preferable that a feed speed of the recording media fed by the third feed means is faster than a feed speed of the recording media fed by the pressure roller. The feed speed of the recording media fed by the first and second feed means may be virtually same as the feed speed of the recording media by the third feed means.

[0015] The foregoing and other objects, advantages, manner of operation and novel features of the present invention will be understood from the following detailed description when read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a front overview for an entire structure of the printer in an

embodiment of the present invention.

[0017] FIG. 2 is an overview for structure of an exposing projector.

[0018] FIG. 3 is an overview for structure of a switchback section.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0019] The following describes in detail an embodiment of the printer according to the present invention in reference to the drawings attached here.

[0020] The printer according to the present invention includes an ink jet printer, a laser printer, and similar printing apparatuses. This embodiment described is for a printer appropriate for Cycolor film (hereinafter referred to as the Cycolor printer), the Cycolor film is a photosensitive recording sheet.

[0021] First, an overview of the Cycolor printer embodied according to the present invention is described below.

[0022] FIG. 1 is a front view illustrating the Cycolor printer 1. A top and a bottom of the figure correspond to those of an apparatus housing 100, and a right and left sides are to those of the apparatus housing 100.

[0023] A media container for media 3, including recording media and film, is arranged in an upper area of the apparatus housing 100. A media unloading port for the media 3 is arranged closed to the media container, on the top of the apparatus housing 100. A feed path is formed from the media container to the media unloading port. Along the feed path are disposed processing sections, including an exposing section, a developing section, and a fixing section. The feed path is disposed in a loop manner inside the apparatus housing 100 as wrapping the processing sections. Parts of the feed path are sharply curved, including a switchback section 64 and an alternative path 121 that will be described later. Such a construction allows every processing section to have space enough to make a single medium stay therein.

[0024] The media container has a cassette room 2 disposed on a side of the apparatus housing 100, on an upper left side in the figure. The cassette

room 2 can load a media cassette 5 therein from a front side in the figure. The media cassette 5 is capable of containing a many number of media 3 for forming desired images. For loading the many number of media 3, they are put downward into the media cassette 5, vertically in the apparatus housing 100 (printer 1). In other words, the many number of media 3 can be loaded so that they can be linearly fed out of the media cassette 5 to the feed path without changing their direction.

[0025] Loading the media cassette 5 in the media container, or the cassette room 2, makes synchronization with a media picking arrangement (not shown) to run a pick roller 101. The pick roller 101 is pressed to the media 3 in the media cassette 5. At the same time, a media pressing arrangement (not shown) is run to press the media 3 in the media cassette 5 to the pick roller 101. As a result, the pick roller 101 can be kept to feed out the media 3 in the media cassette 5 one by one in sequence.

[0026] The cassette room 2 also has a media separating arrangement disposed therein for preventing more than one sheet of the media 3 fed by the pick roller 101 from being fed out to a feed path 51 (which will be described later) at the same time. The media separating arrangement is formed of a pick roller 101 and a separating roller 103 faced and pressed to each other. The feed roller 102 is controlled in rotation so as to feed out the media 3 toward the feed path 51, while the separating roller 103 is controlled in rotation so as to draw back the media 3 toward the pick roller 101. The feed roller 102 in the embodiment is controlled to have greater drive force (torque) than the separating roller 103. Such a media separating mechanism can separate the media 3 fed by the pick roller 101 one by one before feeding to the feed path 51.

[0027] The media 3 is formed of a viscous layer having polyester film coated with a bonding layer and containing numbers of photosensitive microcapsules called Cyliths and a transparent PET (polyethylene terephthalate) layer covering it.

[0028] Each of the microcapsules is filled with a photosensitive agent reactive to a different wavelength and either one of dyes of CYM (cyan, yellow, and magenta). The microcapsule containing the cyan dye is cured with a red light received, that of the yellow dye with a blue light, and that of the magenta with a green light. Microcapsules being not reactive to lights of specific wavelengths and ones receiving no lights cannot be cured. Such microcapsules and a developing and fixing agent called the developer resin are bound to a special oily viscous agent to form the viscous layer.

[0029] Thus, when exposure is made by an exposing projector (which will be described later), red exposure portions have only the cyan dye cured, leaving the other dyes not cured. When a high pressure is applied by a developing roller arranged on the downstream end, the microcapsules containing the yellow dye and the magenta dye are disrupted, resulting in appearance of the red color. Similarly, green exposure portions have only the magenta dye cured, and the microcapsules containing the cyan dye and the yellow dye are destroyed, resulting in appearance of the green color. Blue exposure portions have only the yellow dye cured, and the microcapsules containing the cyan dye and the magenta dye are disrupted, resulting in appearance of the blue color.

[0030] The microcapsule is of a few microns of size. An LCD (liquid display panel) used for printing contains a few capsules per pixel. A curing degree of a microcapsule differs with amount of exposure. These mean that an image of numbers of color gradations can be formed with each microcapsule cured and disrupted depending on color data of each pixel.

[0031] A temperature controlling means (not shown) is disposed at the bottom of the cassette room 2 for controlling environment inside the media cassette 5. In the embodiment is used a Peltier device providing a Peltier effect that can produce temperature difference depending on direction of a current flowing at a junction of dissimilar metals thereof. The Peltier device can be set for either of heating or cooling by controlling the polarity of the

[0036] The exposure path is formed of a pre-stage path 52 disposed in series to the feed path 51 for feeding downstream the media 3 having passed through the feed path 51, an exposing stage 55 disposed downstream in series to the pre-stage path 52, and a post-stage path 57 disposed downstream in series to the exposing stage 55 for feeding the media 3 having passed through the exposing stage 55.

[0037] The exposure path has a plurality of paired rollers therein for feeding downstream the media 3 fed via the feed path 51. In the embodiment are disposed one pair of feed rollers 106 in the pre-stage path 52, three pairs of feed rollers 109, 110, and 111 in the exposing stage 55 at an equal interval, and one pair of feed rollers 112 in the post-stage path 57.

[0038] The exposing stage 55 has a media detecting sensor 113 disposed between the two pairs of feed rollers (between the paired rollers 110 and 111 in the embodiment). According to a sensor signal of the media detecting sensor 113, the media 3 can be halted once at an exposure position on the exposing stage 55. In detail, the media detecting sensor 113 sends the sensor signal out if the media 3 is put at the exposure position on the exposing stage 55 with the media 3 fed on the exposing stage 55 via the pre-stage path 52. At that time, the paired rollers 109, 110, and 111 are controlled to stop from rotating in synchronous with the sensor signal.

[0039] In the state that the media 3 is halted once, the media 3 is exposed separately to three primary color lights, including R (red), G (green), and B (blue), on a printing side 3a thereof (FIG. 2) for a preprocess to form a desired image. It should be noticed that mylar light shields 55a and 55b are arranged on the upstream end and the downstream end of the exposing stage 55 respectively. The light shields 55a and 55b prevent the printing side 3a of the media 3 from being irradiated by external noise lights (disturbing lights) while exposure is made on the exposing stage 55. In addition, a heater (not shown) is disposed on the bottom of the exposing stage 55 to keep the temperature of the exposing stage 55 to a specific value.

The heater can minimize heat radiation of the exposing stage 55.

[0040] An exposing projector 60 as exposure light source is disposed at a position, above around a center of the apparatus housing 100, facing the exposing stage 55. The exposing projector 60 irradiates light to the printing surface 3a of the media 3 for a specific exposure process.

[0041] The exposing projector 60 and the exposing stage 55 in the embodiment are integrated together as an exposing section, or preprocessing means (first processing section) for preprocessing to form the image on the printing surface 3a of the media 3.

[0042] In the exposing projector 60, as shown in FIG. 2, the light radiated from the light source 60a (metal halide lamp) is aligned to a parallel beam through a second optical system 60b (an optical system including a fly array lens and a polarization converter device). The parallel beam then is deflected downward, or toward the exposing stage 55, by a mirror 60c before passing a second optical system 60d having a field lens, a three-color RGB filter driven to rotate, and a wave plate. If the three-color RGB filter is rotated, color image patterns are formed through an LCD panel 60e in timing with respective R, G, and B lights. The image formed on the LCD panel 60e then is projected onto the printing surface 3a of the media 3 on the exposing stage 55 via a deflecting plate 60f and a projecting lens 60g.

[0043] The media 3 having such an exposure process made is transferred to the post-stage path 57 via the paired feed rollers 112 before being controlled to stay on the post-stage path 57 for a specific sensitizing time. The sensitizing time is a period of time needed to develop colors on the exposed media 3 through a developing process (which will be described later) and optimized depending on kind of media 3, exposing time, and other factors. After the sensitizing time elapsed, the media having stayed on the post-stage path 57 is transferred to a feed path 62 via paired feed rollers 114. It should be noticed that the post-stage path 57 is flexed upward (from the bottom to the top of the apparatus housing 100 and is connected with the

feed path 62. The feed path 62 is extended upward inside the apparatus housing 100.

[0044] The 62 formed vertically with respect to the apparatus housing 100 has paired cleaning rollers 115 and switchback section 64 disposed therearound in the order. The exposed media 3 is cleaned by the paired cleaning rollers 115 before being fed to the switchback section 64. In synchronous with feeding of the media 3, a successive media 3 is fed and positioned on the exposing stage 55.

[0045] The exposed media 3 is controlled to stay in the switchback section 64 for a dark time needed for coloring by the developing process (which will be described later). In detail, the switchback section 64 has two pairs of feed rollers 118 and 118 arranged therein along the feed path 62. The feed path 62 between the paired feed rollers 117 and 118 has a media detecting sensor 119 disposed thereon. If the exposed media 3 being fed by the paired feed rollers 117 and 118 reaches a specific position, the media detecting sensor 119 outputs a sensor signal. The paired rollers 117 and 118 are synchronized with the sensor signal to stop. The exposed media 3 is stayed at the specific position in the switchback section 64 for the sensitizing time. For the sensitizing time, the exposed media 3 being successively fed is made to stay on the feed paths 57 and 62 between the exposing stage 55 and the switchback section 64.

[0046] The feed path 62 in the switchback section 64 is extended upward inside the apparatus housing 100 before being broken at around a vertical center of the apparatus housing 100. The media 3 made to stay at the specific position in the switchback section 64 is returned on the same feed path 62 and guided through an alternative path 121 branched from an inlet of the switchback section 64 to a paired pressure developing rollers 68 that is a developing unit (which will be described later).

[0047] Now, the following describes structure, operation, and advantages of the switchback section 64.

[0048] The media 3 exposed on the exposing stage 55 continues photosensitization (exposure reaction) in the microcapsules thereof for a while even after the light irradiation stops. For the reason, the stabilizing time (dark time) for stabilizing the photosensitive reaction in the microcapsules is needed before the microcapsules are fractured by pressure of the paired pressure developing rollers 68. The stabilizing time can be obtained by making longer the feed path from the exposing stage 55 to the paired pressure developing rollers 68. However, arrangement must be made large due to the long feed path accordingly.

[0049] The switchback section 64 therefore is provided to make the media switchback to obtain the dark time needed without making the apparatus large. The paired feed rollers 117 and 118 in the switchback section 64 are arranged so that they can be controlled to drive independently of the other paired rollers, including the paired feed rollers 112 and 114, the paired cleaning rollers 115, and the paired pressure developing rollers 68, the dark time for reaching the paired pressure developing rollers 68 can be changed, made longer or shorter, freely by adjusting the staying time of the media 3 in the switchback section 64.

[0050] In other words, the embodiment uses separate driving controls: the control for the paired feed rollers 112 and 114 and the paired cleaning rollers 115 (first feed means) arranged on the upstream sides of the feed paths 57 and 62 from the above-mentioned exposing section to the paired pressure developing rollers 68 (developing section; and, the control for the paired feed rollers 117 and 118 (second feed means) arranged in the switchback section 64 on the downstream side of the feed path 62. This can make either one of the drivings start while the other stop or the both drivings start or stop to set the dark time to a desired value.

[0051] In detail, as shown in Fig. 3, the paired feed rollers 117 are connected to the motor 141 via the gear arrangement 140, and the paired feed rollers 117 and 118 are linked together by the endless belt 142. In the

embodiment, a switchback driving arrangement is the general term for the paired feed rollers 117 and 118, gear arrangement 140, and the motor 141. The switchback driving arrangement alone can be controlled separately and independently of the other driving arrangement in the apparatus housing 100.

[0052] In such a construction, if the motor 141 is rotated, say, normally, the normal rotational motion is transmitted to the paired feed rollers 117 via the gear arrangement 140 to rotate the paired feed rollers 117 normally. The normal rotational motion of the paired feed rollers 117 is transmitted to the paired feed rollers 118 via the endless belt 142 to rotate paired feed rollers 118 normally as the paired feed rollers 117 and the paired feed rollers 118 are linked together by the endless belt 142. With the paired feed rollers 117 and 118 rotated normally, the media 3 is taken onto the feed path 62 before being stopped at the specific position in the switchback section 64.

[0053] When the dark time elapses, the paired feed rollers 117 and 118 are controlled to rotate in reverse direction if the paired pressure developing rollers 68 are synchronized with the paired feed rollers 117 and 118 in the switchback section 64, that is, if no preceding media 3 exists between the paired pressure developing rollers 68 for development. If the motor 141 is rotated inversely, the inverse rotational motion is transmitted to the paired feed rollers 117 via the gear arrangement 140 to rotate the paired feed rollers 117 and 118 inversely. As a result, the media 3 is fed in the reverse direction on the same

[0054] In the embodiment, a switching gate 120 is disposed on the feed path 62 between the paired feed rollers 117 and the paired cleaning rollers 115. The switching gate 120 is actuated in synchronous with the reverse rotations of the paired feed rollers 117 and 118, the reverse rotations being given by the switchback driving arrangement. The switching gate 120 is supported on the rotating shaft 143. The rotating shaft 143 is linked with the actuator 145 via the linking arrangement 144. The actuator 145 used in the embodiment is of a solenoid. The linking arrangement 144 converts the linear

apparatus housing 100. The alternative path 121 has a plurality of paired feed rollers (two pairs in the embodiment, 122 and 123) provided in a course thereof. The media 3 having the development process made by the paired pressure developing rollers 68 is stabilized in the colorization while being fed on the alternative path 121 by the paired feed rollers 122 and 123.

[0057] In other words, the colorization needs some time (wait time) until the ink exudation stabilizes even after release of the pressure by the paired pressure developing rollers 68. To secure the wait time, it is preferable that length of the alternative path 121 should be made longer. It should be noticed that the alternative path 121 can be set to a desired length according to the switchback distance of the switchback section 64. This allows the wait time to be set depending on the kind of ink used.

[0058] On the upstream of the paired feed rollers 122 is disposed a media detecting sensor 125. If a downstream edge of the media 3 fed on the alternative path 121 passes the media detecting sensor 125, a signal output of the media detecting sensor 125 synchronizes a cutting arrangement 72 to run, which will be described later.

[0059] A high-speed feed path 124 is provided in connection with an end of the alternative path 121 and extended through a top right side of the apparatus housing 100 to an outlet placed on a top left side of the apparatus housing 100.

[0060] For the high-speed feed path 124 are provided paired high-speed feed rollers 126 and the cutting arrangement 72. The paired high-speed feed rollers 126 are controlled to rotate at the same rate as or a little faster than the feed rollers provided in the apparatus housing 100 except for the paired pressure developing rollers 68 at least. The cutting arrangement 72 is arranged on the top of the apparatus housing 100 (top right side looking on the drawing) and serves to cut four margins of the media 3.

[0061] The cutting arrangement 72 has paired slit roller 72a provided for cut out the both right and left side margins of the media 3 fed to come

thereto and a cutter 72b for cutting out a leading and trailing end margins of the media 3. In the embodiment is arranged the paired slitter rollers 72a on the upstream side of the high-speed feed path 124 and at the top corner of the apparatus housing 100 and is arranged the cutter 72b on the virtually horizontal path on the downstream side thereof. Alternatively, the cutter 72b may be arranged on the upstream of the high-speed feed path 124, and the paired slitter rollers 72a may be arranged on the downstream side thereof.

[0062] With the cutting arrangement 72, first the media 3 is cut out on both right and left side margins of a leading half thereof by the paired slitter rollers 72a while being fed, second is halted and cut out on the leading end margin by the cutter 72b, third is restarted to feed and cut out on both right and left side margins of a trailing half thereof by the paired slitter rollers 72a, and fourth is halted again and cut out on the trailing end margin by the cutter 72b. For the cutting operation, a media detecting sensor 128 is arranged in front of an upstream end of the cutter 72b to always sense the leading and trailing end positions of the media 3 being fed on the upstream and downstream ends, thereby controlling timing of cutting out the leading end margin and the trailing end margin of the media 3 by the cutter 72b. It should be noticed that the paired slitter rollers 72a are controlled to rotate at the same rate as the paired high-speed feed rollers 126.

[0063] Below the cutting arrangement 72 (higher portion of the apparatus housing 100) is arranged a containing section 75 for containing the margins cut out of the media 3 therein, or the margin dust cut out by the cutting arrangement 72 drops into the containing section 75 to collect. In actual operation, the environment in the apparatus tends to generate static electricity as the atmosphere is at high temperature and the cut material is of polyester. The static electricity causes sticking of the cut margins when the margins of the media 3 are cut by the paired slitter rollers 72a and the cutter 72b, resulting in hard dropping of the margins and sticking on the inlet. For

should be driven a little slower than the ones arranged in the other feed paths in view of fast continuous process of the media 3, as the bleaching exposure has to be made for a specific time for a desired effect.

[0069] On the downstream end of the bleaching section 77, or at the top left side of the apparatus housing 100, is disposed the outlet in which the post-heating section 80 is arranged.

[0070] The post heating is to make a heating process for accelerating the coloring process as the coloring takes long time until the die (ink) develops its primary color. The post heat is made at 90 degrees C for one minute to virtually saturate exudation of the die, thereby preventing color change afterwards.

[0071] Making the media 3 stay on the feed path is limited in connection with the media 3 for continuous printing process to form the image on the media 3 and lowers the production capability as will be described later. For the reason, the post-heating section 80 in the embodiment is formed of a room for continuously stacking the media 3 vertically at a specific position and a temperature control arrangement, including a sensor and a heater, for keeping the room at a specific temperature. The room temperature is controlled to the desired one of 90 degrees C mentioned above.

[0072] The bleached media 3 in the post-heating section 80 is led to paired retention guides (not shown) facing each other before position on leads (not shown) of lead screws 131. The lead screws 131 are at positions at which four corners of the media 3 can be stably supported. In the state, the paired retention guides are saved away once before the lead screws 131 are rotated one turn to move the media 3 down by one lead. The paired retention guides 83 then are returned to the media bringing position to position the following media 3 at the leads of the lead screws 131.

[0073] Such a repeated operation, including bringing the media 3, positioning, and moving down, makes the media 3 stay in the post-heating section 80. For the duration, the media 3 is heated by a heater (not shown)

to fully develop the colors and prevent aging.

[0074] The lead screws 131 are further turned to make the media 3 discharge onto a discharge tray (not shown) via a feed belt (not shown) in ascending order.

[0075] Corners 146 and 147 on the feed path of the printer 1 constructed as described above are formed to curve at a curvature corresponding to a shape and dimensions of the apparatus housing 100. The corner 146 and 147 has one or a plurality of urging rollers provided for urging the media 3. The embodiment has one urging roller 148 disposed inside the corner 146 and has two urging rollers 149 and 150 disposed inside the corner 147. The urging rollers 148, 149, and 150 are structured to urge the media 3 outward from the printing surface 3a side when the media 3 passes the corners 146 and 147. If the printing surface 3a is urged directly on the printing area thereof, the printing surface 3a is injured. To avoid this, the urging rollers 148, 149, and 150 in the embodiment are arranged to urge (press) edges surrounding the printing area of the printing surface 3a at specific urging forces. It should be noticed that the urging force can be optimized depending on the type of media 3, the feed speed, and the curvatures of the corners.

[0076] The injuries on the media 3a are virtually not distinctive if the urging rollers 148, 149, and 150 have no sharp edges on portions, or ends thereof, contacting the media 3 and if the rollers are made of comparatively soft material. In such a case, the urging rollers 148, 149, and 150 can be urged on the printing area of the media 3a. Such a structure provides the advantages that the media 3 of different width can be passed and that the media 3 can be fed normally even with poor edge positioning accuracy due to possible feed skew.

[0077] The structure in the embodiment has the advantage that the media 3 can pass the corners 146 and 147 stably without deviation in the feed direction while the media 3a is protected. The edges of the media 3 have no

problem for scarring due to the urging rollers since they are cut out by the cutting arrangement 72.

[0078] The following describes operation of the Cycolor printer configured as described above briefly.

[0079] When printing is started in the state that the media cassette 5 is loaded in the cassette room 2, the media 3 fed from the media cassette 5 by pick roller 101 are fed out one by one to the feed path 51 by the media separating arrangement, including the feed roller 102 and the separating roller 103, before being fed from the pre-stage path 52 to the exposing stage 55. The exposing stage 55 stops the media 3 once. The exposing projector 60 irradiates light onto the printing surface 3a of the media 3 on the basis of a desired image pattern, thereby making the exposure process as a preprocess for forming the desired image.

[0080] After the exposure process ends, the exposed media 3 is transferred to the post-stage path 57 with the media 3a directed up and specifically cleaned by the paired cleaning rollers 115 before being fed through the feed path 62 to the switchback section 64.

[0081] The switchback section 64 allows the exposed media 3 to stay for a time (dark time) enough to fully develop its colors. It should be noticed that the successive media 3 fed after are made to stay on the feed paths 57 and 62 between the exposing stage 55 and the switchback section 64. After that, the preceding media 3 is fed back on the feed path 62 again at a specific timing as the paired feed rollers 117 and 118 are controlled to rotate inversely.

[0082] The media 3 fed back on the feed path 62 is fed to the alternative path 121 via the switching gate 120, is guided to the paired pressure developing rollers 68, and has surface load applied to the both sides thereof, thereby forming (color-developing) the desired image.

[0083] The media 3 having the development process completed is continued to feed along parts of the surface on one of the paired pressure

developing rollers 68 to transfer from the alternative path 121 to the high-speed feed path 124, is checked for paper jamming in the course of feed by the paper jam detecting sensor 127, and is fed to the cutting arrangement 72.

[0084] The media 3 having the four side edges cut out by the cutting arrangement 72 is bleaching-processed (ink-fixing-processed) during passing the bleaching section 77, is discharged to the take-out part (post-heating section 80) on the top left side of the apparatus housing 100. It should be noticed that the media detecting sensor 129 arranged in front of the upstream side of the post-heating section 80 controls the discharge timing for the media 3.

[0085] As described above in detail, the printer in the embodiment comprises in combination for forming an image on a surface of a recording media: preprocessing means for preprocessing the surface of the recording media to form an image on the surface of the recording media; post-processing means for post-processing the surface of the recording means preprocessed by the preprocessing means to form the image on the surface of the recording media; a recording media feed path formed between the preprocessing means and the post-processing means; first feed means arranged on an upstream side of the recording media feed path; and, second feed means arranged on a downstream side of the recording media feed path; wherein the first feed means and the second feed means are made different in driving control from each other. Thus, the printer can print a plurality of recording media successively that no large-scale arrangements are provided for printing processes to meet a required printing accuracy and to shorten a processing time.

[0086] In particular, the printer further comprises a switchback section for substantially extending the recording media feed path wherein the second feed means is provided in the switchback section. The switchback section has a switchback path installed therein vertically and the second feed means

is arranged on the switchback path and has a switchback driving arrangement for independently driving the second feed means. Therefore, the printer can be built up at low price as suppressing apparatus manufacturing costs with use of simple feed driving arrangements and controls. With the switchback path arranged, the media 3 discharged onto a discharge tray (not shown) after printing is finished can be checked without turning it over as the media 3a appears up.

[0087] Further, the feed speed of the media 3 fed by the plurality of feed means arranged on the feed path for the media 3 is optimized for driving control. The printer does not make the feed path for the recording media long to prevent the apparatus from becoming large while securing a stabilizing time (dark time) until the photosensitive reaction in the microcapsules of the media 3 stabilizes.

[0088] With use of the structures described above, as a result, pressure destruction of the microcapsules by the paired pressure developing rollers 68 in the developing section can be made stably and securely, thereby improving quality of the media 3a.

[0089] Further, the printer 1 in the embodiment has the urging rollers 148, 149, and 150 disposed on the corners 146 and 147 of the feed path for urging the edges of the media 3a of the media 3. It is advantageous that the media 3 can pass the corners 146 and 147 stably without deviation in the feed direction while the media 3a is protected.

[0090] The present invention is not limited to the embodiment described above, but can be modified in many ways as follows.

[0091] In the embodiment, the switching gate 120 in the switchback section 64 is driven by the actuator 145 to rotate. Instead, for example, the switching gate 120 may be made up of an elastic material. In that case, the feed path should be switched over in the way that the actuator 145 should elastically deform the elastic material by linear motion of thereof.

[0092] In place of the switchback section 64, an additional feed path similar

to the feed path 62 may be provided in parallel with the feed path 62 to have different driving controls for the feed rollers arranged on the respective feed paths. In that case, it is preferable that a switching gate should be disposed at a branch point of the feed paths to guide the media 3 from the media cassette 57 to either of the feed path 62 or the feed path arranged in place of the switchback section 64.

[0093] The embodiment of the present invention has been described in detail with the example of Cycholor type printer suitable for the Cycholor film as a photosensitive recording sheet. The present invention can also be embodied for printers of other different types.

05964503 112001